



We CARE About Reliability and Performance!

| KOMATSU CARE D65EX / EXi / PX / PXi / WX-18 | | | | |
|--|----------|----------|----------|----------|
| PM Interval | 500 | 1000 | 1500 | 2000 |
| KOWA SAMPLES (engine, transmission, hydraulic, I/r final drives) | / | ✓ | √ | ✓ |
| LUBRICATE MACHINE | ✓ | ✓ | ✓ | ✓ |
| CHANGE ENGINE OIL | / | / | ✓ | ✓ |
| REPLACE ENGINE OIL FILTER | / | / | / | / |
| REPLACE FUEL PRE- FILTER | 1 | / | / | / |
| CLEAN FUEL STRAINER | / | / | / | / |
| REPLACE POWER TRAIN OIL FILTER | 1 | / | 1 | / |
| DRAIN FUEL TANK SEDIMENT | 1 | 1 | 1 | / |
| REPLACE A/C FRESH AND RECIRCULATION FILTERS | 1 | / | 1 | / |
| CLEAN AIR CLEANER ELEMENT | 1 | / | 1 | / |
| COMPLETE 50 POINT INSPECTION FORM; LEAVE PINK COPY WITH CUSTOMER OR IN CAB | / | ✓ | √ | √ |
| RESET MONITOR PANEL MAINTENANCE COUNTER FOR APPROPRIATE ITEMS | / | 1 | √ | ✓ |
| REPLACE FUEL MAIN FILTER | | 1 | | / |
| CHANGE POWER TRAIN OIL | | / | | / |
| CLEAN POWER TRAIN STRAINER | | / | | / |
| CLEAN SCAVENGING PUMP STRAINER | | / | | / |
| CHECK DAMPER CASE OIL LEVEL | | / | | / |
| CHANGE FINAL DRIVE OIL | | / | | / |
| REPLACE HYDRAULIC TANK BREATHER ELEMENT | | / | | / |
| REPLACE FUEL TANK BREATHER ELEMENT | 1 | / | | 1 |
| REPLACE DEF TANK BREATHER ELEMENT | | / | | / |
| CLEAN POWER TRAIN CASE BREATHER | | / | | / |
| CHANGE HYDRAULIC OIL | | | | / |
| REPLACE HYDRAULIC FILTER | | | | 1 |
| CLEAN HYDRAULIC TANK STRAINER | | | | / |
| CHANGE DAMPER CASE OIL | | | | 1 |
| REPLACE KCCV FILTER | 1 | | | / |
| REPLACE DEF FILTER | 1 | | | 1 |
| FACTORY TRAINED TECHNICIAN LABOR | 1 | / | / | <u> </u> |
| 2 KDPF Exchanges at 4,500 Hrs and 9,000 Hrs. | 1 * | . · | ı * | |
| 2 SCR System Maintenance Services at 4,500 Hrs. and 9000 Hrs. | | | | |
| Total Value for Komatsu CARE | | | \$9,7 | 64.20 |



KOMATSU CARE

Program Includes:

*The D65EX-18 comes standard with complimentary factory scheduled maintenance for the first 3 years or 2,000 Hours, whichever comes first.

Planned Maintenance Intervals at:

500/1000/1500/2000 hour intervals. (250 hr. initial interval for some products) Complimentary Maintenance Interval includes: Replacement of Oils & Fluid Filters with genuine Komatsu Parts, 50-Point inspection, Komatsu Oil & Wear Analysis Sampling (KOWA) / Travel & Mileage (distance set by distributor; additional charges may apply)

Benefits of Using Komatsu CARE

- Assurance of Proper Maintenance with OEM Parts & Service
- Increased Uptime & Efficiency
- Factory Certified Technicians Performing Work
- Cost of Ownership Savings
- Transferable Upon Resale

Complimentary KDPF Exchange

The D65EX-18 comes standard with 2 Complimentary KDPF Exchange Units for the first 5 years (unlimited hours) Complimentary KDPF Exchange Units are provided at: The suggested KDPF Exchange Units Service Intervals of 4,500 hours and 9,000 hours during the first 5 years. End User must have authorized Komatsu distributor perform the removal and installation of the KDPF.

Complimentary SCR System Maintenance

The D65EX-18 also includes 2 factory recommended services of the Selective Catalytic Reduction (SCR) Diesel exhaust fluid (DEF) system during the first 5 years—no hour limit—including:

 Factory recommended DEF tank flush and strainer cleaning at 4,500 hours and 9,000 hours

