



# We CARE About Reliability and Performance!

KOMATSU CARE PC390LC-11					
Interval PM	500	1000	1500	2000	
KOWA SAMPLING (engine, hydraulics, swing circle, I & r final drives)	1	1	<b>/</b>	<b>√</b>	
LUBRICATE MACHINE	/	/	/	<b>/</b>	
LUBRICATE SWING CIRCLE	/	/	/	<b>/</b>	
CHECK SWING PINION GREASE LEVEL AND ADD, WHEN NECESSARY	1	1	1	<b>√</b>	
CHANGE ENGINE OIL	1	<b>/</b>	<b>✓</b>	<b>√</b>	
REPLACE ENGINE OIL FILTER	/	1	/	<b>/</b>	
REPLACE FUEL PRE FILTER	/	1	/	/	
REPLACE AIR CONDITIONER FRESH/RECIRC FILTERS	1	1	/	<b>√</b>	
CLEAN AIR CLEANER ELEMENT	1	1	/	<b>√</b>	
DRAIN SEDIMENT FROM FUEL TANK	1	1	/	1	
COMPLETE 50 POINT INSPECTION FORM; LEAVE PINK COPY WITH CUSTOMER OR IN CAB	1	1	1	1	
RESET MONITOR PANEL MAINTENANCE COUNTER FOR APPROPRIATE ITEMS	1	1	1	<b>✓</b>	
REPLACE HYDRAULIC TANK BREATHER ELEMENT		<b>/</b>		<b>√</b>	
REPLACE DEF TANK BREATHER ELEMENT		1		<b>√</b>	
CHECK DAMPER CASE OIL LEVEL, ADD WHEN NECESSARY		1		<b>/</b>	
REPLACE FUEL MAIN FILTER		/		/	
CHANGE SWING MACHINERY OIL		1		<b>√</b>	
REPLACE HYDRAULIC OIL FILTER ELEMENT		1		/	
CLEAN HYDRAULIC TANK STRAINER				/	
CHANGE FINAL DRIVE OIL				<b>√</b>	
REPLACE KCCV FILTER ELEMENT				<b>/</b>	
REPLACE DEF PUMP FILTER				<b>/</b>	
FACTORY TRAINED TECHNICIAN LABOR	1	1	/	1	
2 KDPF Exchanges at 4,500 Hrs and 9,000 Hrs.					
2 SCR System Maintenance Services at 4,500 Hrs. and 9000 Hrs.					
Total Value for Komatsu CARE			\$8,559.89		





### **KOMATSU CARE**

### **Program Includes:**

\*The PC390LC-11 comes standard with complimentary factory scheduled maintenance for the first 3 years or 2,000 Hours, whichever comes first.

#### Planned Maintenance Intervals at:

500/1000/1500/2000 hour intervals. (250 hr. initial interval for some products) Complimentary Maintenance Interval includes: Replacement of Oils & Fluid Filters with genuine Komatsu Parts, 50-Point inspection, Komatsu Oil & Wear Analysis Sampling (KOWA) / Travel & Mileage (distance set by distributor; additional charges may apply)

#### **Benefits of Using Komatsu CARE**

- Assurance of Proper Maintenance with OEM Parts & Service
- Increased Uptime & Efficiency
- Factory Certified Technicians Performing Work
- Cost of Ownership Savings
- Transferable Upon Resale

# Complimentary KDPF Exchange

The PC390LC-11 comes standard with 2 Complimentary KDPF Exchange Units for the first 5 years (unlimited hours) Complimentary KDPF Exchange Units are provided at: The suggested KDPF Exchange Units Service Intervals of 4,500 hours and 9,000 hours during the first 5 years. End User must have authorized Komatsu distributor perform the removal and installation of the KDPF.

## **Complimentary SCR System Maintenance**

The PC390LC-11 also includes 2 factory recommended services of the Selective Catalytic Reduction (SCR) Diesel exhaust fluid (DEF) system during the first 5 years—no hour limit—including:

 Factory recommended DEF tank flush and strainer cleaning at 4,500 hours and 9,000 hours