



KOMATSU CARE PC650LC-11				
Interval PM	500	1000	1500	2000
KOWA SAMPLING – (Engine, Hydraulics, L & R Swing Machinery, L & R Final Drives)	✓	✓	✓	✓
LUBRICATE MACHINE	1	√	✓	√
LUBRICATE SWING CIRCLE	1	✓	√	✓
CHECK SWING PINION GREASE LEVEL AND ADD, WHEN NECESSARY	✓	✓	✓	✓
CHANGE ENGINE OIL	\checkmark	\checkmark	\checkmark	\checkmark
REPLACE ENGINE OIL FILTER	√	✓	√	\checkmark
REPLACE FUEL PRE-FILTER	1	√	✓	✓
REPLACE AC FRESH & RECIRC AIR FILTERS	1	√	✓	✓
CLEAN PTO STRAINER	1	√	✓	✓
CLEAN AIR CLEANER ELEMENT	1	√	✓	✓
DRAIN SEDIMENT FROM FUEL TANK	1	√	✓	√
COMPLETE 50 POINT INSPECTION FORM; LEAVE PINK COPY WITH CUSTOMER OR IN CAB	✓	✓	✓	✓
RESET MONITOR PANEL MAINTENANCE COUNTER FOR APPROPRIATE ITEMS	✓	✓	✓	✓
REPLACE HYDRAULIC TANK BREATHER ELEMENT		\checkmark		\checkmark
REPLACE DEF TANK BREATHER ELEMENT		√		√
REPLACE FUEL MAIN FILTER		√		√
CHANGE PTO CASE OIL		✓		✓
CHANGE SWING MACHINERY OIL		✓		✓
REPLACE HYDRAULIC OIL FILTER ELEMENT		√		✓
CLEAN HYDRAULIC TANK STRAINER				✓
CHANGE FINAL DRIVE OIL				✓
REPLACE KCCV FILTER ELEMENT				√
REPLACE DEF PUMP FILTER				√
FACTORY TRAINED TECHNICIAN LABOR	1	√	1	√
2 KDPF Exchanges at 4,500 Hrs and 9,000 Hrs.				
2 SCR System Maintenance Services at 4,500 Hrs. and 9000 Hrs.				
Total Value for Komatsu CARE			\$9,649.61	

We CARE About Reliability and Performance!

KOMATSU CARE

Program Includes:

*The PC650LC-11 comes standard with complimentary factory scheduled maintenance for the first 3 Years or 2,000 Hours, whichever comes first.

Planned Maintenance Intervals at:

500/1000/1500/2000 hour intervals. (250 hr. initial interval for some products) Complimentary Maintenance Interval includes: Replacement of Oils & Fluid Filters with genuine Komatsu Parts, 50-Point inspection, Komatsu Oil & Wear Analysis Sampling (KOWA) / Travel & Mileage (distance set by distributor; additional charges may apply)

Benefits of Using Komatsu CARE

- Assurance of Proper Maintenance with OEM Parts & Service
- Increased Uptime & Efficiency
- Factory Certified Technicians Performing Work
- Cost of Ownership Savings
- Transferable Upon Resale

Complimentary KDPF Exchange

The PC650LC-11 comes standard with 2 Complimentary KDPF Exchange Units for the first 5 Years (unlimited hours) Complimentary KDPF Exchange Units are provided at: The suggested KDPF Exchange Units Service Intervals of 4,500 hours and 9,000 hours during the first 5 years. End User must have authorized Komatsu distributor perform the removal and installation of the KDPF.

Complimentary SCR System Maintenance

The PC650LC-11 also includes 2 factory recommended services of the Selective Catalytic Reduction (SCR) Diesel exhaust fluid (DEF) system during the first 5 years—no hour limit—including:

 Factory recommended DEF tank flush and strainer cleaning at 4,500 hours and 9,000 hours

